



DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS LOUVRE FABRICS

product: Polyester Basic B1 9601
quality: see sundrape® drapery designs
louvre width:..... mm
consisting of:

material:
100% polyester

physical characteristics:
weight of material: abt. 210 g/qm
non-fading according to DIN EN 105-B01: 5
opaque
PVC-free coating

	9601	9602	9603	9604
reflexion in %:	78	60	52	17
absorption in %:	2	29	43	82
transmission in %: in %:	20	11	5	1
total energy transmission degree gt:	0,31	0,39	0,43	0,58
reduction factor Fc:	0,44	0,54	0,59	0,81

	9610	9605	9606	9607
reflexion in %:	67	21	33	13
absorption in %:	19	78	64	86
transmission in %: in %:	14	1	3	1
total energy transmission degree gt:	0,36	0,57	0,51	0,60
reduction factor Fc:	0,50	0,79	0,71	0,84

behaviour in fire:
flame resistant according to (DE) DIN 4102 B1

utilization:

In any area of domestic and project buildings, recommended for computer work places according to ISO 9241-6, computer work places decree, to EU regulation (90/270/EWG) and work station regulations (§ 7 und § 9) as well as for humid rooms.