

DETAILED ESTIMATE  
FOR SUNDRAPE ROLLER BLIND SYSTEMS  
DRAPERY QUALITIES



product: Contour I 5800  
quality: see sundrape® drapery designs  
drapery width: 1520 mm  
consisting of:

material:  
PET, präcision blocking foil  
Quality 5800 2R screen stamping  
physical characteristics:  
weight of material: abt. 110 g/qm  
non-fading according to DIN EN 105-B01: 8

|                                      |       |        |       |       |
|--------------------------------------|-------|--------|-------|-------|
| Physikalische Eigenschaften          | 5800  | 5807   | 5808  | 5809  |
| transmission factor:                 | 2,5 % | 17,0 % | 2,3 % | 2,5 % |
| UV- transmission factor:             | 1 %   | 1 %    | 1 %   | 1 %   |
| reflexion in %:                      | 80    | 64     | 79    | 80    |
| absorption in %:                     | 17,5  | 19     | 18,7  | 17,5  |
| transmission in %:                   | 2,5   | 17     | 2,3   | 2,5   |
| total energy transmission degree gt: | 0,29  | 0,38   | 0,30  | 0,29  |
| reduction factor Fc:                 | 0,41  | 0,52   | 0,42  | 0,41  |
| openess factor                       | 2R    | 10R    | 2R    | 2R    |

utilization:

In any area of domestic and project buildings, recommended for computer work places according to ISO 9241-6, computer work places decree, to EU regulation (90/270/EWG) and work station regulations (§ 7 und § 9) as well as for humid rooms.