

DETAILED ESTIMATE
FOR SUNDRAPE ROLLER BLIND SYSTEMS
DRAPERY QUALITIES



product: Interloon® Screen I 430
quality: see sundrape® drapery designs
drapery width: 2400 mm
consisting of:

material:
100% polyester
PVC- and halogen-free coating

physical characteristics:

weight of material: abt. 205 g/qm
non-fading according to DIN EN 105-B01: 5
semi transparent

| | 430 | 431 | 432 | 433 |
|--------------------------------------|------|------|------|------|
| reflexion in %: | 54 | 53 | 45 | 36 |
| absorption in %: | 2 | 8 | 17 | 35 |
| transmission in %: | 44 | 39 | 38 | 29 |
| total energy transmission degree gt: | 0,45 | 0,45 | 0,49 | 0,49 |
| reduction factor Fc: | 0,62 | 0,63 | 0,68 | 0,68 |

| | 434 | 435 | 436 | 437 | 438 |
|--------------------------------------|------|------|------|------|------|
| reflexion in %: | 7 | 25 | 8 | 26 | 5 |
| absorption in %: | 83 | 55 | 83 | 57 | 88 |
| transmission in %: | 10 | 20 | 9 | 17 | 7 |
| total energy transmission degree gt: | 0,53 | 0,51 | 0,52 | 0,48 | 0,64 |
| reduction factor Fc: | 0,74 | 0,70 | 0,73 | 0,67 | 0,89 |

behaviour in fire:
flame resistant according to (DE) DIN 4102 B1

Öko-Tex Standard 100

moisture proof
moisty wiping

utilization:
In any area of domestic and project buildings.