

# DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System Corvus A1  
with vertical textile louvres  
quality: see louvres collection  
louvre width: 90 and 127 mm,  
consisting of:

Rail:  
width: 33 mm, height 36 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or colour coated according to RAL.

Runners:  
The runners made of acetate-chromate resistant to wear and tear have a slide bearing. The built-in slip clutch avoids destroying of the carriers in case of false handling. The louvre hooks are made of high-tensile Makrolon, which is light-proof, UV-fast and flame retardant as per DIN 4102 B1.

Louvres:  
The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard), do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed, they are flame retardant as per DIN 4102 B1 respectively are fireproof finished according to DIN 4102 A2.  
The sealed-in plastic slat holders are hung into the gear carriers which run in the top rail.  
Vertical and parallel alignment of the louvres by full-plastic bottom weights which are interconnected by plastic link chains with reversers.

Control:  
Rotation (150°) and traversing of the louvres is effected by means of a buckled crank.