

DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System **sundrape® Future Colour Line**

with vertical textile louvres
quality: see louvres collection
louvre width:mm
consisting of:

Rail:

width: 40 mm, height: 25 mm, narrow rail opening of 10 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or colour coated as per RAL.

Colour of the plastic parts:

drive unit gear: red
distance chain: red
end cap: blue
cord: blue
operating chain: green
chain
cord weight: yellow

Runners:

The runners (7 mm wide) are made of acetate-chromate, resistant to wear and tear, with slide bearing for small louvre stacks. Integrated link adjusters allow guiding to the end caps. The built-in slip clutch avoids destroying the runners in case of false handling. The louvre hooks are of high-tensile Makrolon, light-proof, UV-fast and flame retardent as per DIN 4102 B1. They are exchangeable without demounting the top rail.

Louvres:

The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard). They do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed. They have flame retardent finish as per DIN 4102 B1 or fireproof according to DIN 4102 A2.

The sealed-in plastic slat holders are hooked into the gear carriers which are guided in the top rail.

Vertical and parallel alignment of the louvres by fully plastic bottom weights which are interconnected by plastic link chains with reversers.

Control:

Tilting (180°) of the louvres by means of a laterally fixed endless plastic bead chain. Traversing movement of the one-part or split louvre blind by cordpull.