

# DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System **sundrape® Future New Look**  
with vertical textile louvres  
quality: see louvres collection  
louvre width: .....mm  
consisting of:

## Rail:

width: 40 mm, height: 25 mm, narrow rail opening of 10 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or colour coated as per RAL.

## Colour of the plastic parts

Endcaps, operating cord and operating chain of this system are black coloured.

## Runners:

The runners (7 mm wide) are made of acetate-chromate, resistant to wear and tear, with slide bearing for small louvre stacks. Integrated link adjusters allow guiding to the end caps. The built-in slip clutch avoids destroying of the runners in case of false handling. The louvre hooks of high-tensile Makrolon, light-proof, UV-fast and flame retardent as per DIN 4102 B1 are exchangeable without demounting the top rail.

## Louvres:

The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard) , they do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed. Flame retardent finish as per DIN 4102 B1 or fireproof according to DIN 4102 A2.

The sealed-in plastic slat holders are hooked into the gear carriers which are guided in the top rail.

Vertical and parallel alignment of the louvres by fully plastic bottom weights which are interconnected by plastic link chains with reversers.

## Control:

Tilting (180°) of the louvres by means of a laterally fixed endless plastic bead chain. Traversing movement of the one-part or split louvre blind by cordpull.