

DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System sundrape® Palma P9
with vertical textile louvres
quality: see louvres collection
louvre width: mm
consisting of:

Rail:

width: 44,5 mm, height: 25 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or colour coated as per RAL.

Runners:

The runners (9 mm wide) made of acetate-chromate resistant to wear have a roller bearing. The built-in slip clutch avoids destroying the runners in case of false handling. The louvre hooks are made of high-tensile Makrolon, light-proof, UV-fast and flame retardent as per DIN 4102 B1.

Louvres:

The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard) they do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed. Flame retardent as per DIN 4102 B1 or fireproof according to DIN 4102 A2.

The sealed-in plastic slat holders are hooked into the gear carriers which are guided in the top rail.

Vertical and parallel alignment of the louvres by fully plastic bottom weights which are interconnected by plastic link chains with reversers.

Control:

Tilting (180°) of the louvres by means of a laterally fixed endless plastic bead chain via reduction gear.

Traversing movement of the one-part or split louvre blind by cordpull.