

# DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System Palma Slope A1 with vertical textile louvres  
quality: see louvres collection  
louvre width: ..... mm  
consisting of:

Rail:  
width: 44.5 mm, height: 25 mm, made of extruded aluminium AlMgSi 0.5 F22,  
technically anodized as per E6/EV1 or colour coated according to RAL.

Runners:  
The runners (11 mm wide) made of acetate-chromate resistant to wear and tear, have a roller bearing. The built-in slip clutch avoids destroying of the carriers in case of false handling. The louvre hooks are made of high-tensile Makrolon, light-proof, UV-fast and flame retardent as per DIN 4102 B1 and are exchangeable ex cardan joint without having to demount the rail.

Louvres:  
The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard) , they do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed. Flame retardent properties as per DIN 4102 B1 or fireproof finish according to DIN 4102 A2.  
The sealed-in plastic slat holders are hung into the gear carriers running in the top rail. The gear carriers have cardanic louvre hangers made of polycarbonate, and link holders of stainless steel (0.3 mm thick).  
Vertical and parallel alignment of the louvres by fully plastic bottom weights which are interconnected by plastic link chains with reversers.

Control:  
Rotation (180°) of the louvres by means of a laterally fixed endless plastic bead chain via reduction gear.  
Traversing movement of the one-part or split louvre blind by cordpull.

System Palma Rod A1