

DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System **sundrape® Star Kurbelmatic**
with vertical textile louvres
quality: see louvres collection
louvre width: mm
consisting of:

Rail:
width: 45.5 mm, height: 36.5 mm, made of extruded aluminium AlMgSi 0.5 F22,
technically anodized as per E6/EV1 or colour coated according to RAL.

Runners:
The runners (11 mm wide) are made of acetate-chromate resistant to wear and tear
with roller bearing for small louvre stacks. The built-in slip clutch avoids destroying
the runners in case of false handling.

Louvres:
The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial
Standard), do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can
be washed and ironed, they are flame retardant as per DIN 4102 B1 or have a
fireproof finish according to DIN 4102 A2.
The sealed-in plastic slat holders are hooked into the gear carriers which are running
in the rail.
Vertical and parallel alignment of the louvres by fully plastic bottom weights which are
inter-connected by plastic link chains with reversers.

Operation:
Tilting (150°) und traversing of the louvres by means of a laterally fixed operation
crank. The crank is also removable available. The special gear automatically first tilts
and then traverses the louvres.