

# DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



## System Star Mono A2

with textile louvres which are vertically fixed between top and bottom rail

quality: see louvres collection

louvre width:.....mm

consisting of:

## Rail:

width: 45 mm, height: 36.5 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or colour coated according to RAL.

## Runners:

The runners (11 mm wide) made of acetate-chromate resistant to wear and tear have a roller bearing. The built-in slip clutch avoids destroying of the carriers in case of false handling.

## Louvres:

The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard), do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed, they are flame retardant as per

DIN 4102 B1 respectively are fireproof finished according to DIN 4102 A2.

The sealed-in plastic slat holders are stress-fixed between springy stainless steel hooks in the self-adjusting gear carriers, guided in the rails.

## Control:

Rotation (150°) and traversing of the louvres is effected by a lateral endless plastic bead chain over a special sundrape gear.

Rotation and traversing of the louvres can be made with one pull.

## Dust cover:

When the bottom rail is mounted flush with the floor the bottom rail can alternatively have a dust cover.