

# DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



## **sundrape® Star Mono Slope**

system sundrape® Star Mono Slope (Slopematic) with vertical textile louvres  
quality: see sundrape® vertical blind collection  
louvre width: \_\_\_\_\_ mm

consisting of:

### **Rail**

width: 45 mm, height: 36,5 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or white colour coated according to RAL 9016

### **Runners**

The runners (11 mm wide), made of acetate-chromate, are resistant to wear and tear with roller bearing. The built-in slip clutch avoids destroying the runners in case of false handling. The louvre hooks of high-tensile Makrolon, light-proof, UV-fast and flame retardant as per DIN 4102 B1 are exchangeable from cardan joint without demounting the rail.

### **Louvres**

The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard), do not shrink nor lengthen, they are bacteriostatic, moisture-proof and can be washed and ironed. They are flame retardant as per DIN 4102 B1 or have a fireproof finish according to DIN 4102 A2.

The sealed-in plastic slat holders are hooked with polycarbonat cardan suspension and spacers of stainless steel into the gear carriers which are running in the rail.

Vertical and parallel alignment of the louvres by fully plastic bottom weights which are inter-connected by plastic link chains with reversers.

### **Control**

Tilting (180°) and traversing of the louvres by means of a laterally fixed endless plastic bead chain via special sundrape® gear.