

DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System Star Zug A1 with vertical textile louvres
quality: see louvres collection
louvre width: mm
consisting of:

Rail:
width: 45.5 mm, height: 36.5 mm, made of extruded aluminium AlMgSi 0.5 F22,
technically anodized as per E6/EV1 or colour coated according to RAL.

Runners:
The runners (9 mm wide) made of acetate-chromate resistant to wear and tear with roller bearing for small louvre stacks going up to the endcaps. The built-in slip clutch avoids destroying of the carriers in case of false handling. The louvre hooks of high-tensile Makrolon, light-proof, UV-fast and flame retardent as per DIN 4102 B1 are exchangeable without demounting the rail.

Louvres:
The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard), do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed, they are flame retardent as per DIN 4102 B1 or have a fireproof finish according to DIN 4102 A2.
The sealed-in plastic slat holders are hung into the gear carriers which are running in the rail.
Vertical and parallel alignment of the louvres by fully plastic bottom weights which are inter-connected by plastic link chains with reversers.

Control:
Rotation (180°) of the louvres by means of a laterally fixed endless plastic bead chain via reduction gear.
Traversing movement of the one-part or split louvre blind by cordpull, facilitated by large traversing rolls.