

# DETAILED ESTIMATE FOR SUNDRAPE VERTICAL BLINDS



System Star Zug A2 with textile louvres which are vertically fixed between top and bottom rail

quality: see louvres collection

louvre width: ..... mm

consisting of:

Rail:

width: 45 mm, height: 36.5 mm, made of extruded aluminium AlMgSi 0.5 F22, technically anodized as per E6/EV1 or colour coated according to RAL.

Runners:

The runners (11 mm wide) made of acetate-chromate resistant to wear and tear have a roller bearing. The built-in slip clutch avoids destroying of the carriers in case of false handling.

Louvres:

The louvres are highly light-fast as per DIN EN 105-B01 (German Industrial Standard), do not shrink nor lengthen, they are bacteriostatic, damp-proof, and can be washed and ironed, they are flame retardant as per

DIN 4102 B1 respectively are fireproof finished according to DIN 4102 A2.

The plastic slat holders which are sealed in the louvres are stress-fixed on springy stainless steel hooks of the gear carriers which run in the rails.

Control:

Rotation (180°) of the louvres is effected by means of a laterally fixed endless plastic bead chain via reduction gear.

Traversing of the one-part or split drapery is effected by cordpull.

Dust Cover:

When the bottom rail is mounted flush with the floor the rail can alternatively have a dust cover.