

## Movable roller blind type D 7060

Movable roller blind type D 7060 based on side pull roller blind type D 7540 with mounting profile and operating rod

### Draperies

Please see *sundrapé®* collection

### Maximum sizes

width min/max 400/2300 mm

height 3000 mm depending on chosen drapery and direction of fabrication

### Roller blind shaft

extruded aluminium high-precision profile, AIMgSi0,5 F22, Ø 40 x 2 mm  
special inner profile to guarantee twist-safe power transmission

### Side pull gear

ball chain gear, integrated roll-down safety device, type plastic white, inserted into roller blind shaft in a twist-safe way, drapery weight 3 kg max

### Mounting angle

solid, galvanized sheet steel support, white powder-coated, fixed with mounting profile

### Mounting profile

extruded aluminium flat profile, AIMgSi0,5 F22, sizes 40 x 4 mm, to take up roller blind mounting support and plastic runner, white powder coated according to RAL 9016

### Bottom bar

extruded aluminium hollow profile, AIMgSi 0,5 F22, width 11 mm, height 41 mm, fixing with flat bar, E6/EV1 naturally anodized or white powder-coated as to RAL 9016, brush profile optional

### Control

continuous control by pulling the ball chain; two chain locks/stopper fix drapery's upper and lower end position; ball chain made of plastic or special steel, moving per operating rod in the panel curtain rail; assembly of max. two movable roller blinds type D 7060 in a row in a 5-track panel curtain rail

### Mounting

wall, ceiling or niche mounting  
hooked in rail channel with plastic runners, rail channel on both sides equipped with damper for lateral stop

### Combination with panel curtain

Movable roller blinds can be combined with free movable panel curtains; split-up of number of track channels on request

More details of panel curtain rails please look up in detailed estimate for panel curtains

