

DETAILED ESTIMATE SUNDRAPE ROLLER



Sidepull Roller Type 6000

for draperies see roller blinds collection
maximum sizes width min/max 400/2000 mm, height 3000 mm
depending on the chosen drapery and the
direction of fabrication

Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm

Sidepull gear

bead chain gear, integrated rolling-down safety device, plastic white or brown, inserted in the roller shaft in a twist-safe way, drapery weight 2 kg max.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 52 mm, height 47.5 mm, side parts made of plastic white or brown, roller to be clicked in via clips nose.

Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 5.5 mm, height 25 mm, inserted in drapery seam.

Side guiding

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 37 mm, height 14 mm, hidden fixing screws for wall or window niche, covering profile to be clipped in.

Control

continuous control by pulling the bead chain. Two chain locks serve as top and bottom end position of the roller drapery.

Mounting

wall, ceiling, window niche. Screwed through back part of the casing.

Variants

type 6020 with additional bottom latching rail.
type 6030 like type 6000, however, width of side guiding 57 mm
type 6040 like type 6020, however, width of side guiding 57 mm