

DETAILED ESTIMATE SUNDRAPE ROLLER



Sidepull Roller Type 6010

for draperies see roller blinds collection
maximum sizes width min/max 400/2000 mm, height 3000 mm
 depending on the chosen drapery and the
 direction of fabrication

Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm

Sidepull gear

bead chain gear, integrated rolling-down safety device made of plastic white or brown, inserted in the roller shaft in a twist-safe way, drapery weight max 2 kg.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1-anodized, powder coated white RAL 9016 or brown 8014, 2 parts, width 52 mm, height 48 mm, side parts made of plastic white or brown, roller to be clicked in via clips nose.

Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 5,5 mm, height 25 mm, inserted in drapery seam.

Control

continuous control by pulling the bead chain. Two chain locks serve as top and bottom end position of the roller drapery.

Mounting

wall, ceiling, window niche. Screwed through back part of the casing.

Variants

type 6011 with tension wire guiding, fixing at wall/ceiling/window niche.
 Tension wire nature or white, alu bottom rail E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 1 part, open, fixing of drapery by inserted flat bar, also available with brush profile, width 8 mm, height 30 mm.