

DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6110

for draperies see roller blinds collection

maximum sizes width min/max 400/1400 mm, height 3800 mm
depending on the chosen drapery and the
direction of fabrication

Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm

Electro control

tubular motor 24V, motor inserted in the roller blind shaft in a twist-safe way, drapery weight up to 5 kg max., end position switch-off at the top/bottom, 40 limit switch rotations.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 52 mm, height 47,5 mm, side parts made of plastic white or brown, roller can be clicked in over clips nose.

Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 5.5 mm, height 25 mm, inserted in drapery seam.

For foil drapery: extruded aluminium profile 1 part with flat bar, width 8 mm, height 30 mm.

Control

electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

Mounting

wall, ceiling, window niche. Screwed through back side of casing.

Variants

type 6150 with tension wire guiding, fixing wall, ceiling, window niche.
Tension wire natural colour or white, alu bottom rail E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, fixing of drapery by inserted flat bar, width 8 mm, height 30 mm.