

DETAILED ESTIMATE SUNDRAPE ROLLER



Sidepull Roller Type 6200

for draperies see roller blinds collection
maximum sizes width min/max 400/2000 mm, height 3000 mm
 depending on the chosen drapery and the
 direction of fabrication

Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm.

Sidepull gear

bead chain gear, integrated rolling down safety device, type plastic white or brown, inserted in roller shaft in a twist-safe way, drapery weight max 2 kg.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic white or brown, roller can be clicked in over clips nose.

Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 5,5 mm, height 25 mm, inserted in drapery seam.

For foil drapery: extruded aluminium profile 1 part with flat bar, width 8 mm, height 30 mm.

Side guiding

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 57 mm, height 22 mm, covered fixing screws at the wall/window niche, cover profile can be clipped.

Control

continuous control by pulling the bead chain. Two chain locks serve as top and bottom end position of the roller blind drapery.

Mounting

wall, ceiling, window niche. Screwed through back part of the casing.

Variants

type 6220 with additional bottom latching rail.