

# DETAILED ESTIMATE SUNDRAPE ROLLER



## Sidepull Roller Type 6250

for draperies            see roller blinds collection  
maximum sizes        width min/max 600/2200 mm, height 3000 mm,  
                                 depending on the chosen drapery and the  
                                 direction of fabrication.

### Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 38 x 1 mm.

### Sidepull gear

bead chain gear, integrated rolling down safety device, type plastic white, inserted in the roller shaft in a twist-safe way, drapery weight max 3 kg.

### Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic white or brown, roller can be clicked in over clips nose.

### Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 11 mm, height 41 mm, 2 parts, open, fixed by fixing device in drapery seam, E6/EV1 natural anodized, powder coated white RAL 9016 or brown RAL 8014.

### Side guiding

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 57 mm, height 22 mm, hidden fixing screws at the wall or in window niche, cover profile can be clipped.

### Control

continuous control by pulling the bead chain. Two chain locks serve as top and bottom end position of the roller drapery.

### Mounting

wall, ceiling, window niche. Screwed through back part of casing.

### Variants

type 6260    like type 6250, however, without side guiding.