

# DETAILED ESTIMATE SUNDRAPE ROLLER



## Sidepull Roller Type 6270

for draperies                                    see roller blinds collection  
maximum sizes                                width min/max 400/2200 mm, height 3000 mm  
depending on the chosen drapery and the  
direction of fabrication.

Roller blind shaft  
extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm.

Sidepull gear  
bead chain gear, integrated rolling down safety device, type plastic white or brown, inserted  
in the roller shaft in a twist-safe way, drapery weight max 2 kg.

Roller casing  
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL  
9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic  
white or brown, roller can be clicked in over clips nose.

Bottom rail  
extruded aluminium profile AlMgSi 0.5 F22, width 11 mm, height 41 mm, 1 part with flat bar,  
open, fixed by fixing device in drapery seam, E6/EV1 natural anodized, powder coated white  
RAL 9016 or brown RAL 8014.

Side guiding  
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL  
9016 or brown RAL 8014, one part, width 68 mm, height 22 mm, with brush inserts, hidden  
fixing screws for the window niche.

Control  
continuous control by pulling the bead chain. Two chain locks serve as top and bottom end  
position of the roller drapery.

Mounting  
wall, ceiling, window niche. Screwed through back of casing. For wall mount side guidings  
with cover caps in fixing drillings.

Variants  
type 6290    like type 6270, however, with roller shaft 38 x 1 mm.