

DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6300

for draperies
maximum sizes

see roller blinds collection
width min/max 400/2000 mm, height 3800 mm
depending on the chosen drapery and the
direction of fabrication.

Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm.

Electro control

tubular motor 24V, motor inserted in the roller blind shaft in a twist-safe way, drapery weight up to 5 kg max., end position switch-off at the top/bottom, 40 limit switch rotations.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic white or brown, roller can be clicked in over clips nose.

Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 5.5 mm, height 25 mm, inserted in drapery seam.

For foil drapery: extruded aluminium profile 1 part with flat bar, width 8 mm, height 30 mm.

Side guiding

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, two parts, width 57 mm, height 22 mm, hidden fixing screws for wall and window niche fixing, cover profile can be clipped.

Control

electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

Mounting

wall, ceiling, window niche. Screwed through back of casing.

Variants

type 6230 with additional latching bottom rail.