

DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6310

for draperies see roller blinds collection
maximum sizes width min/max 400/2000 mm, height 3800 mm depending on the chosen drapery and the direction of fabrication.

Roller blind shaft
extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm.

Electro control
tubular motor 24V, motor inserted in the roller blind shaft in a twist-safe way, drapery weight up to 5 kg max., end position switch-off at the top/bottom, 40 limit switch rotations.

Roller casing
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic white or brown, roller can be clicked in over clips nose.

Bottom rail
extruded aluminium profile AlMgSi 0.5 F22, width 5.5 mm, height 25 mm, inserted in drapery seam.

Control
electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

Mounting
wall, ceiling, window niche. Screwed through back of casing.

Variants type 6350 with tension wire guiding, fixing at the wall, ceiling, window niche. Tension wire nature coloured or white, alu bottom rail E6/EV1 anodized, powder coated white RAL 9016 or brown 8014, 1 part, open, fixing of drapery by inserted flat bar, also available with brush profile, width 11 mm, height 41 mm.