

DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6400

for draperies see roller blinds collection
maximum sizes width min/max 700/2500 mm, height 4000 mm depending on the chosen
 drapery and the direction of fabrication.

Roller blind shaft
extruded aluminium profile AlMgSi 0.5 F22, diameter 42 x 2 mm.

Electro control
tubular motor 230V/50Hz/130W, torque 3 Nm, VDE-EMV approved, VDE, CE, motor
inserted in the roller shaft in a twist-safe way, 30 axial RPM, end position switch-off at the
top/bottom.

Roller casing
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL
9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic
white or brown, roller can be clicked in over clips nose.

Bottom rail
extruded aluminium profile AlMgSi 0.5 F22, width 11 mm, height 41 mm, one part, fixing of
drapery by inserted flat bar, E6/EV1 natural anodized, powder coated white RAL 9016 or
brown RAL 8014.

Side guiding
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL
9016 or brown RAL 8014, 2 parts, width 57 mm, height 22 mm, hidden fixing screws for wall
and window niche mount, cover profile can be clipped.

Control
electrically over touch/caged switch or radio remote control individually or in groups, with
overriding central control or via brightness controller.

Mounting
wall, ceiling, window niche. Screwed through back of casing.

Variants
type 6420 with additional latching rail at the bottom.