## DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6410

for draperies see roller blinds collection width min/max 700/2500 mm, height 4000 mm depending on the chosen drapery and the direction of fabrication.

Roller blind shaft extruded aluminium profile AlMgSi 0.5 F22, diameter 42 x 2 mm.

Electro control

tubular motor 230V/50Hz/130W, torque 3 Nm, VDE-EMV approved, VDE, CE, motor inserted in the roller shaft in a twist-safe way, 30 axial RPM, end position switch-off at the top/bottom.

## Roller casing

extruded aluminium profile AIMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL 9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic white or brown, roller can be clicked in over clips nose.

## Bottom rail

extruded aluminium profile AIMgSi 0.5 F22, width 10 mm, height 41 mm, one part, fixing of drapery by inserted flat bar, E6/EV1 natural anodized, powder coated white RAL 9016 or brown RAL 8014.

Control

electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

Mounting

wall, ceiling, window niche. Screwed through back of casing.

Variants

type 6411 with tension wire guiding, fixing at the wall, ceiling, window niche, tension wire nature-coloured or white.