

# DETAILED ESTIMATE SUNDRAPE ROLLER



## Electro Roller Type 6700

for draperies                    see roller blinds collection  
maximum sizes                width min/max 700/2700 mm, height 4000 mm depending on the chosen  
    drapery and the direction of fabrication.

## Roller blind shaft

round tube made of aluminium, diameter 50 x 1,5 mm.

## Electro control

tubular motor 230V/50Hz/130W, torque 3 Nm, VDE-EMV approved, VDE, CE, motor inserted in the roller shaft in a twist-safe way, 30 axial RPM, end position switch-off at the top/bottom.

## Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL 9016, 3 parts, width 102 mm, height 102 mm, side parts made of aluminium EV1 or white.

## Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 11 mm, height 41 mm, one part, fixing of drapery by inserted flat bar, E6/EV1 natural anodized or powder coated white RAL 9016.

## Side guiding

extruded aluminium profile AlMgSi 0.55 F22, E6/EV1 anodized or powder coated white as to RAL 9016, two parts, width 57 mm, height 22 mm, covered fixing screws for the wall or window niche, cover profile clipsable.

## Control

electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

## Mounting

wall, ceiling, window niche. Screwed through back of casing.

## Variants

type 6720    with additional latching rail at the bottom.