DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6710

for draperies see roller blinds collection

maximum sizes width min/max 700/2700 mm, height 4000 mm depending on the chosen

drapery and the direction of fabrication.

Roller blind shaft

round tube made of aluminium, diameter 50 x 1,5 mm.

Electro control

tubular motor 230V/50Hz/130W, torque 3 Nm, VDE-EMV approved, VDE, CE, motor inserted in the roller shaft in a twist-safe way, 30 axial RPM, end position switch-off at the top/bottom.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL 9016, 3 parts, width 102 mm, height 102 mm, side parts made of aluminium EV1 or white.

Bottom rail

extruded aluminium profile AIMgSi 0.5 F22, width 11 mm, height 41 mm, one part, fixing of drapery by inserted flat bar, E6/EV1 natural anodized or powder coated white RAL 9016.

Control

electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

Mounting

wall, ceiling, window niche. Screwed through back of casing.

Variants

type 6711 with tension wire guiding, fixing at the wall, at the ceiling, in window niche,

tension wire and fixing angle, natural coloured or white.