

# DETAILED ESTIMATE SUNDRAPE ROLLER



## Electro Roller Type 6770

for draperies                      see roller blinds collection  
maximum sizes                  width min/max 700/2700 mm, height 4000 mm depending on the chosen  
drapery and the direction of fabrication.

Roller blind shaft  
round tube made of aluminium, diameter 50 x 1,5 mm.

Electro control  
tubular motor 230V/50Hz/130W, torque 3 Nm, VDE-EMV approved, VDE, CE, motor  
inserted in the roller shaft in a twist-safe way, 30 axial RPM, end position switch-off at the  
top/bottom.

Roller casing  
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL  
9016, 3 parts, width 102 mm, height 102 mm, side parts made of aluminium EV1 or white.

Bottom rail  
extruded aluminium profile AlMgSi 0.5 F22, width 11 mm, height 41 mm, one part, fixing of  
drapery by inserted flat bar, E6/EV1 natural anodized or powder coated white RAL 9016.

Side guiding  
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL  
9016, one-part, width 68 mm, height 22 mm, with brush inserts, covered fixing screws for  
mounting in the niche.

Control  
electrically over touch/caged switch or radio remote control individually or in groups, with  
overriding central control or via brightness controller.

Mounting  
wall, ceiling, window niche. Screwed through back of casing.