

# DETAILED ESTIMATE SUNDRAPE ROLLER



## Electro Roller Type 6800

for draperies                      see roller blinds collection  
maximum sizes                  width min/max 800/3300 mm, height 4000 mm depending on the chosen  
drapery and the direction of fabrication.

### Roller blind shaft

anodized round tube made of precision steel, diameter 63 x 1,5 mm.

### Electro control

tubular motor 230V/50Hz/135W, torque 8 Nm, VDE-EMV approved, VDE, CE, motor  
inserted in the roller shaft in a twist-safe way, 14 axial RPM, end position switch-off at the  
top/bottom.

### Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL  
9016, 3 parts, width 102 mm, height 102 mm, side parts made of aluminium EV1 or white.

### Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 11 mm, height 41 mm, one part, fixing of  
drapery by inserted flat bar, E6/EV1 natural anodized or powder coated white RAL 9016.

### Side guiding

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL  
9016, two parts, width 57 mm, height 22 mm, covered fixing screws for mounting at the wall  
or in the window niche, cover profile clipsable.

### Control

electrically over touch/caged switch or radio remote control individually or in groups, with  
overriding central control or via brightness controller.

### Mounting

wall, ceiling, window niche. Screwed through back of casing.

### Variants

type 6820      with additional latching rail at the bottom.