DETAILED ESTIMATE SUNDRAPE ROLLER



Electro Roller Type 6910

for draperies see roller blinds collection

maximum sizes width min/max 1000/4000 mm, height 4000 mm depending on the

chosen drapery and the direction of fabrication.

Roller blind shaft

anodized round tube made of precision steel, diameter 83 x 1,5 mm.

Electro control

tubular motor 230V/50Hz/200W, torque 20 Nm, VDE-EMV approved, VDE, CE, motor inserted in the roller shaft in a twist-safe way, 15 axial RPM, end position switch-off at the top/bottom.

Roller casing

extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized or powder coated white RAL 9016, 3 parts, width 102 mm, height 102 mm, side parts made of aluminium EV1 or white.

Bottom rail

extruded aluminium profile AIMgSi 0.5 F22, width 11 mm, height 41 mm, one part, fixing of drapery by inserted flat bar, E6/EV1 natural anodized or powder coated white RAL 9016.

Control

electrically over touch/caged switch or radio remote control individually or in groups, with overriding central control or via brightness controller.

Mounting

wall, ceiling, window niche. Screwed through back of casing.

Variants

type 6870 with side guiding: extruded aluminium profile AIMgSi 0.5 F22, E6/EV1 anodized

or powder coated white RAL 9016, one-part, width 68 mm, height 22 mm, with

brush inserts, covered fixing screws for niche mount.