

Technical specifications

sundrape® roller blind with headbox "Hercules Auto-Stop" 7072

Examples of application

Large sized roller blind, hand operation, mounting above windows and glass fronts, freely suspended, wall mounting, ceiling mounting or niche mounting

Fabrics

see sundrape® roller blind collection

Sizes

minimum width: 1200 mm
maximum width: 3500 mm
maximum height: 4000 mm
depending on selected fabric

Fabric weight

including bottom bar
minimum: 2,0 kg
maximum: 6,0 kg

Roller blind shaft

extruded aluminium tube with special inner profile AlMgSi0,5F22 diameter 55 mm fixing of drapery by inserted bar.

Driving mechanism

sidepull drive with ball chain control, comfortable auto-stop safety device, step-down gear for heavy weight roller blind fabrics, damped clutch with integrated roll down safety device, inserted in roller shaft in a twist-free way

Headbox

extruded aluminium profile, in three parts, front cover profile 20° sloped, removable, dimensions 102x102 mm lateral aluminium covering caps

Bottom bar

extruded aluminium profile AlMgSi0,5F22, one part, dimensions: 11 x 41 mm, with hollow cell for weighting pieces made of galvanized steel, plastic end caps, white or light grey, fixing of drapery by inserted flat bar, also available with brush profile.

Mounting

Wall mounting of headbox with screws through headbox rear part or ceiling mounting with screws through headbox top part.

Operation

continuous control by pulling the front ball chain:
a slight pull of the front chain makes the drapery roll down.
let the chain glide through your hand, then at the desired position of the drapery, let go of ball chain: the roller blind drapery will stop.

Colours

Aluminium profiles powder coated, white RAL 9016 or anodized in EV1, natural-coloured, lateral parts: same colour as colour of headbox, plastic parts white.