

# DETAILED ESTIMATE SUNDRAPE ROLLER



## Soft Roller Type 7100

for draperies            see roller blinds collection  
maximum sizes        width min/max 400/2000 mm, height 3800 mm  
                                 depending on the chosen drapery and direction  
                                 of fabrication.

## Roller blind shaft

extruded aluminium profile AlMgSi 0.5 F22, diameter 28 x 0,7 mm

## Electro motor

tubular motor 24V, motor inserted in the roller blind shaft in a twist-safe way, drapery weight up to 5 kg max., end position switch-off at the top/bottom, 40 limit switch rotations.

## Mounting angle

made of full plastic white or brown, screwed to top rail, roller can be clipped in over clips nose.

## Bottom rail

extruded aluminium profile AlMgSi 0.5 F22, width 5,5 mm, height 25 mm, inserted in drapery seam.

For foil drapery: extruded aluminium profile 1 part with flat bar, width 8 mm, height 30 mm.

## Control

electrically via touch/caged switch or radio remote control, individually or in groups, with overriding central control or via brightness controller.

## Mounting

wall, ceiling, window niche.

## Variants

type 7111    with tension wire guiding, fixing in window niche

type 7112    with tension wire guiding, wall mounting

type 7113    with tension wire guiding, ceiling mount.

tension wire natural or white, alu bottom rail E6/EV1-anodized, powder coated white RAL 9016 or brown RAL 8014, 1 part, fixing of drapery by inserted flat bar, also available with brush profile, width 8 mm, height 30 mm.