



## Technical Specifications

roller blind sundrape, type M 1212

### Examples of application

in front or underneath window niche, above fixed glass elements, on or above doors, universal wall or ceiling mounting

### Fabrics

see sundrape roller blinds collection

### Maximum sizes

min. width: 350 mm  
max. width: 2000 mm  
max. height: 3000 mm  
depending on selected fabric

### Cassette

extruded aluminium profile  
AlMgSi0,5 F22, one part  
dimensions: 49 x 54 mm

### Roller blind shaft

extruded aluminium tube  
with special inner profile  
AlMgSi0,5 F22  
diametre 30 mm

### Sidepull control

control by ball chain,  
integrated rolling down safety device  
inserted in roller shaft in a twist-free way  
drapery weight 2,0 kg max.

### Lateral guiding

SunTape side guiding profile, 2 parts  
back screwed or taped  
glare protection profile can be clipped on  
fabric held by tapes sealed onto fabric edges  
extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 28 x 14 mm

### Bottom bar

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 10 x 23 mm  
inserted flat bar

### Mounting

screwed aluminium clip support, coloured like cassette for wall and ceiling mounting, roller blind can be clicked

### Control options

continuous control by pulling ball chain  
plastic ball chain with ball distance 6 mm;  
chain locks stop top and bottom position of the fabric.

Alternative control elements:  
chain made of stainless steel

### Colours

Profile powder coated white 9016 or silver 9006,  
side parts and control elements black or white

### Accessories

chain holder self-adhesive  
aluminium clamp support