



Technical Specifications

roller blind sundrape, type M 1312

Examples of application

in front or underneath window niche, above fixed glass elements, on or above doors, universal wall or ceiling mounting

Fabrics

see sundrape roller blinds collection

Maximum sizes

min. width: 350 mm
max. width: 2000 mm
max. height: 3000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22, one part
dimensions: 49 x 54 mm

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre 30 mm

Sidepull control

control by ball chain,
integrated rolling down safety device
inserted in roller shaft in a twist-free way
drapery weight 2,0 kg max.

Lateral guiding

U - side guiding profile, 1 part
extruded aluminium profile
AlMgSi0,5 F22
provided with screw thread for mounting in niches; for wall mounting sticking optional
dimensions 28 x 14 mm

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 10 x 23 mm
inserted flat bar

Mounting

screwed aluminium clip support, coloured like cassette for wall and ceiling mounting, roller blind can be clicked

Control options

continuous control by pulling ball chain
plastic ball chain with ball distance 6 mm;
chain locks stop top and bottom position of the fabric.

Alternative control elements:
chain made of stainless steel

Colours

Profile powder coated white 9016 or silver 9006,
side parts and control elements black or white

Accessories

chain holder self-adhesive
aluminium clamp support