



Technical Specifications

roller blind sundrape, type M 2212

Examples of application

in front or underneath window niche, above fixed glass elements, on or above doors, universal wall or ceiling mounting

Fabrics

see sundrape roller blinds collection

Maximum sizes

min. width: 350 mm
max. width: 2000 mm
max. height: 3000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22, one part
dimensions: 49 x 54 mm

Roller blind shaft

circular aluminium tube
diametre 29 mm

Electric operation

low voltage motor 24V D.C.
inserted in roller shaft in a twist-free way
mechanical fixing of end position
drapery weight 4,0 kg max.

Lateral guiding

SunTape side guiding profile, 2 parts
back screwed or taped
glare protection profile can be clipped on
fabric held by tapes sealed onto fabric edges
extruded aluminium profile
AlMgSi0,5 F22
dimensions 28 x 14 mm

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 10 x 23 mm
inserted flat bar

Mounting

screwed aluminium clip support, coloured like cassette for wall and ceiling mounting, roller blind can be clicked

Control options

concealed or not concealed switch
single or in groups, central push button for group operation, radio remote control

Colours

Profile powder coated white 9016 or silver 9006,
side parts and control elements black or white

Accessories

aluminium clamp support