



## Technical Specifications

roller blind sundrape, type M 2312

### Examples of application

in front or underneath window niche, above fixed glass elements, on or above doors, universal wall or ceiling mounting

### Fabrics

see sundrape roller blinds collection

### Maximum sizes

min. width: 350 mm  
max. width: 2000 mm  
max. height: 3000 mm  
depending on selected fabric

### Cassette

extruded aluminium profile  
AlMgSi0,5 F22, one part  
dimensions: 49 x 54 mm

### Roller blind shaft

circular aluminium tube  
diametre 29 mm

### Electric operation

low voltage motor 24V D.C.  
inserted in roller shaft in a twist-free way  
mechanical fixing of end position  
drapery weight 4,0 kg max.

### Lateral guiding

U - side guiding profile, 1 part  
extruded aluminium profile  
AlMgSi0,5 F22  
provided with screw thread for mounting in niches; for wall mounting sticking optional  
dimensions 28 x 14 mm

### Bottom bar

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 10 x 23 mm  
inserted flat bar

### Mounting

screwed aluminium clip support, coloured like cassette for wall and ceiling mounting, roller blind can be clicked

### Control options

concealed or not concealed switch  
single or in groups, central push button for group operation, radio remote control

### Colours

Profile powder coated white 9016 or silver 9006,  
side parts and control elements black or white

### Accessories

aluminium clamp support