



Technical Specifications

roller blind sundrape, type M 3712 (shaft at the bottom)

Examples of application

on window or door casement, in front of window niche, especially recommended for computer work places

Fabrics

see sundrape roller blinds collection

Maximum sizes

min. width: 350 mm
max. width: 2000 mm
max. height: 2000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22, one part
dimensions: 49 x 54 mm
installation at the bottom

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22, one part
diametre 30 mm
twist-free inserted spring motor

Cord control

cordpull integrated invisibly in the side guiding; end cap of the side guiding with cord deflection and locking roll; operating cord 1.5 mm with knob, safety device for drapery; two cord coilers for winding up the cord

Colours

Profile powder coated white 9016 or silver 9006,
side parts and control elements black or white

Lateral guiding

SunTape side guiding profile, 2 parts
glare protection profile can be clipped on fabric held by tapes sealed onto fabric edges
extruded aluminium profile
AlMgSi0,5 F22
dimensions 28 x 14 mm

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22; plastic endcaps
dimensions 10 x 23 mm
inserted flat bar

Mounting

clip support for ceiling and wall mounting,

Control

continuous control by pulling the cord knob when the cord is in diagonal position fabric is stopped by vertical cord guiding