

# Technical Specifications

## sundrape roller blind, type L 1312



### Examples of application

in front or underneath window niche, above fixed glass elements  
universal wall or ceiling mounting  
especially suited for black out purposes

### Fabrics

see sundrape roller blind collection

### Maximum sizes

minimum width: 500 mm  
maximum width: 2500 mm  
maximum height: 4000 mm  
depending on selected fabric

### Head box

extruded aluminium profile  
AlMgSi0,5 F22, in two parts  
dimensions: 73 x 77 mm

### Roller blind shaft

extruded aluminium tube  
with special inner profile  
AlMgSi0,5 F22  
diametre 42 mm

### Sidepull control

control by ball chain,  
power reduced control by planet gear  
integrated rolling down safety device  
inserted in roller shaft in a twist-free way  
stopper plates for end position  
drapery weight 3,5 kg max.

### Lateral guiding

extruded aluminium profile  
AlMgSi0,5 F22, in two parts  
dimensions: 58 x 20 mm  
rear part fixed with hidden screw, cover profile with clip, brush seal for black out, bottom plastic cover, additional black out foamy seal tape

### Bottom bar

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 12 x 28 mm  
inserted flat bar  
brush seal for black out at the bottom  
plastic end caps sliding in lateral guiding

### Mounting

screwed aluminium clip support,  
for wall and ceiling mounting,  
roller blind can be clicked  
lateral guiding fixed with hidden screws

### Control options

continuous control by pulling ball chain  
plastic ball chain with ball distance 6 mm;  
alternative: stainless steel chain or plastic ball chain with ball distance 12 mm

### Colours

profile powder coated white 9016 or silver 9006, side parts and control elements black or white

### Accessories

chain holder with screw