

Technical Specifications

sundrape roller blind, type L 1412



Examples of application

in front or underneath window niche, above fixed glass elements, universal wall or ceiling mounting

Fabrics

see sundrape roller blind collection

Maximum sizes

minimum width: 500 mm
maximum width: 2500 mm
maximum height: 4000 mm
depending on selected fabric

Head box

extruded aluminium profile
AlMgSi0,5 F22, in two parts
dimensions: 73 x 77 mm

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre: 42 mm

Sidepull control

control by ball chain,
power reduced control by planet gear
integrated rolling down safety device
inserted in roller shaft in a twist-free way
stopper plates for end position
drapery weight 3,5 kg max.

Tension wire guiding

to prevent drapery from floating
plastic-coated tension wire coloured like side parts, tension support with covered suspension clamp for wall and niche mounting

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 12 x 28 mm
inserted flat bar

Mounting

screwed aluminium clip support for wall and ceiling mounting, roller blind can be clicked

Control options

continuous control by pulling ball chain
plastic ball chain with ball distance 6 mm;
alternative: stainless steel chain or plastic ball chain with ball distance 12 mm

Colours

profile powder coated white 9016 or silver 9006,
side parts and control elements black or white

Accessories

chain holder with screw