

Technical Specifications

sundrape roller blind, typ L 1912



Examples of application

in front or underneath window niche, above fixed glass elements, universal wall or ceiling mounting especially suited for black out purposes

Fabrics

see sundrape roller blind collection

Maximum sizes

minimum width: 500 mm
maximum width: 2500 mm
maximum height: 4000 mm
depending on selected fabric

Head box

extruded aluminium profile
AlMgSi0,5 F22, in two parts
dimensions: 73 x 77 mm

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre: 42 mm

Sidepull control

control by ball chain,
power reduced control by planet gear
integrated rolling down safety device
inserted in roller shaft in a twist-free way
stopper plates for end position
drapery weight 3,5 kg max.

Lateral guiding / sink profile

extruded aluminium profile
AlMgSi0,5 F22, in two parts
dimensions 58 x 20 mm
rear part fixed with hidden screw, cover
profile with clip, brush seal for black out,
sink down profile with brush seal for an
effective black out at bottom
sink profile covering side guiding and
screwed complete additional black out foamy
seal tape

Bottom bar

extruded aluminium profile AlMgSi0,5 F22
dimensions 12 x 28 mm inserted flat bar
brush seal for black out at the bottom,
plastic end caps sliding in lateral guiding

Mounting

screwed aluminium clip support for wall and
ceiling mounting, roller blind can be clicked
lateral guiding fixed with hidden screws

Control options

continuous control by pulling ball chain
plastic ball chain with ball distance 6 mm;
alternative: stainless steel chain or plastic
ball chain with ball distance 12 mm

Colours

profile powder coated white 9016 or
silver 9006, side parts and control elements
black or white

Accessories

chain holder with screw