# **Technical Specifications**

# sundrape roller blind, type L 2912



## **Examples of application**

in front or underneath window niche, above fixed glass elements universal wall or ceiling mounting

#### **Fabrics**

see sundrape roller blind collection

#### **Maximum sizes**

minimum width: 600 mm maximum width: 2500 mm maximum height: 4000 mm depending on selected fabric

#### **Head box**

extruded aluminium profile AlMgSi0,5 F22, in two parts dimensions: 73 x 77 mm

#### Roller blind shaft

extruded aluminium tube with special inner profile AIMgSi0,5 F22 diametre 42 mm

#### **Electric drive**

tube motor 230 V/ 50 Hz, torque 3 Nm speed: 30 rpm, mechanic limit switch with a capacity of 29 rpm; alternative: tube motor with integrated radio receiver, programming via mounting cable or handsender. drapery weight 7,0 kg max. motor inserted in roller shaft in a twist-free way

# Lateral guiding / sink profile

extruded aluminium profile
AlMgSi0,5 F22, in two parts
dimensions 58 x20 mm
rear part fixed with hidden screw, cover
profile with clip, brush seal for black out,
sink down profile with brush seal for an
effective black out at bottom
sink profile covering side guiding and
screwed, complete additional black out
foamy seal tape

#### **Bottom bar**

extruded aluminium profile
AIMgSi0,5 F22
dimensions 12 x 28 mm
inserted flat bar
brush seal for black out at the bottom,
plastic end caps sliding in lateral guiding

### Mounting

screwed aluminium clip support, for wall and ceiling mounting, roller blind can be clicked lateral guiding fixed with hidden screws

## **Control options**

control with switch, concealed or not concealed, or via comfort control unit for single control or group control with additional central control radio remote control, single or in groups

#### Colours

profile powder coated white 9016 or silver 9006, side parts and control elements black or white

#### **Accessories**

a large variety of control and operation elements for single, group, central and radio control