



Technical Specifications

roller blind sundrape, type S 1210

Examples of application

in front or into window niche,
on window or door casement

Fabrics

see sundrape roller blinds collection

Sizes

min. width: 350 mm
max. width: 1500 mm
max. height: 2000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22
dimensions: 43 x 45 mm
open in the back for ventilation purposes

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre 26 mm

Sidepull control

control by ball chain or cord
integrated rolling down safety device
inserted in roller shaft in a twist-free way
drapery weight 1.5 kg max.

Colours

Profiles powder-coated white 9016 or
silver 9006
side parts and control elements black or
white

Lateral guiding

SunTape side guiding profile, 2 parts
glare protection profile can be clipped on
fabric held by tapes sealed onto fabric
edges
extruded aluminium profile
AlMgSi0,5 F22
dimensions 28 x 14 mm

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 10 x 23 mm
inserted flat bar

Mounting

clip support for wall- or ceiling mounting
clamp support alternatively

Control options

continuous control by pulling ball
chain or control cord
plastic ball chain with ball distance 6
2 chain locks stop top and bottom
position of the fabric.
alternative control elements:
chain made of stainless steel or control
cord, diametre 4 mm