



## Technical Specifications

roller blind sundrape, type S 1310

### Examples of application

on window or door casement, in front of window niche

### Fabrics

see sundrape roller blinds collection

### Sizes

min. width	350 mm
max. width	1500 mm
max. height	2000 mm

depending on selected fabric

### Cassette

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions: 43 x 45 mm  
open in the back for ventilation purposes

### Roller blind shaft

extruded aluminium tube  
with special inner profile  
AlMgSi0,5 F22  
diametre 26 mm

### Sidepull control

control by ball chain or cord  
integrated rolling down safety device  
inserted in roller shaft in a twist-free way  
drapery weight 1.5 kg max.

### Colours

Profiles powder-coated white 9016 or silver 9006  
side parts and control elements black or white

### Lateral guiding

U-side guiding profile, 1 parts  
provided with screw thread for mounting in niches, for wall mounting sticking optional  
extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 28 x 14 mm

### Bottom bar

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 10 x 23 mm  
inserted flat bar

### Mounting

clip support for wall- or ceiling mount, clamp support alternatively

### Control options

continuous control by pulling ball chain or control cord  
plastic ball chain with ball distance 6  
2 chain locks stop top and bottom position of the fabric.  
alternative control elements:  
chain made of stainless steel or control cord, diametre 4 mm