



Technical Specifications

roller blind sundrape, type S 1620

Examples of application

roller blind for eyeprotection
window or door casement
with rectangular or slanting window
rabbets

Fabrics

see sundrape roller blinds collection

Sizes

min. width: 350 mm
max. width: 1500 mm
max. height: 2000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22
dimensions: 43 x 45 mm
open in the back for ventilation purposes

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre 26 mm

Sidepull control

control by ball chain or cord,
integrated rolling-down safety device,
inserted in roller shaft in a twist-free way
weight of fabric 1.5 kg max.

Colours

profile powder coated white 9016 or silver
9006
side parts and control elements black or
white

Lateral guiding

antiglare profiles at both sides,
self-adhesive, 46 mm width
extruded aluminium profile
AlMgSi0,5 F22
glue-fixed on front of window rabbet

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 10 x 23 mm
inserted flat bar

Mounting

set of antiglare caps with screwed
supports for mounting between the
window rabbets

Control

continuous control by pulling the ball
chain or the control chain
plastic ball chain with ball distance 6
2 chain locks act as stoppers for the
top and bottom position of the roller blind
fabric
alternative control elements:
chain made of stainless steel or control
cord, diametre 4 mm