



Technical Specifications

roller blind sundrape, type S 3310

Examples of application

in front or into window niche,
on window or door casement

Fabrics

see sundrape roller blinds collection

Sizes

min. width: 350 mm
max. width: 1500 mm
max. height: 2000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22
dimensions: 43 x 45 mm
open in the back for ventilation purposes

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre 26 mm

Cord control

winding spindle, inserted in roller shaft in
a twist-safe way
cord deflection with locking roll
control cord 1.5 mm with knob
drapery saving device

Colours

profile powder coated white 9016 or silver
9006
side parts and control elements black or
white

Lateral guiding

U-side guiding profile, 1 parts
provided with screw for mounting in
niches, for wall mounting sticking
optional
extruded aluminium profile
AlMgSi0,5 F22
dimensions 28 x 14 mm

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 10 x 23 mm
inserted flat bar

Mounting

clip support for wall- or ceiling mounting
clamp support alternatively

Control

continuous control by pulling the cord
knob diagonally
fabric is stopped by vertical cord guiding