



## Technical Specifications

roller blind sundrape, type S 3620

### Examples of application

roller blind for eyeprotection  
window or door casement  
with rectangular or slanting window  
rabbets

### Fabrics

see sundrape roller blinds collection

### Sizes

min. width 350 mm  
max. width 1500 mm  
max. height 2000 mm  
depending on selected fabric

### Cassette

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions: 43 x 45 mm  
rear open for ventilation between glass  
and fabric

### Roller blind shaft

extruded aluminium tube  
with special inner profile  
AlMgSi0,5 F22  
diametre 26 mm

### Cord control

winding spindle, inserted in roller shaft in  
a twist-safe way  
cord deflection with locking roll  
control cord 1.5 mm with knob  
fabric is held

### Colours

profile powder coated white 9016 or silver  
9006  
side parts and control elements black or  
white

### Lateral guiding

antiglare profiles at both sides,  
self-adhesive, 46 mm wide  
extruded aluminium  
AlMgSi0,5 F22  
glue-fixed on front of window rabbet

### Bottom bar

extruded aluminium profile  
AlMgSi0,5 F22  
dimensions 10 x 23 mm  
inserted flat bar

### Mounting

set of antiglare caps with screwed  
supports for mounting between the  
window rabbets

### Control

continuous control by pulling the cord  
knob diagonally  
fabric is stopped by vertical cord guiding