



Technical Specifications

roller blind sundrape, type S 3710 (shaft at the bottom)

Examples of application

on window or door casement, in front of window niche, especially recommended for computer work places

Fabrics

see sundrape roller blinds collection

Sizes

min. width: 350 mm
max. width: 1500 mm
max. height: 2000 mm
depending on selected fabric

Cassette

extruded aluminium profile
AlMgSi0,5 F22
dimensions: 43 x 45 mm
installation at the bottom

Roller blind shaft

extruded aluminium tube
with special inner profile
AlMgSi0,5 F22
diametre 26 mm
spring motor inserted in a twist-safe way

Cord control

cordpull integrated invisibly in the side guiding; end cap of the side guiding with cord deflection and locking roll; operating cord 1.5 mm with knob, safety device for drapery; two cord coiler for winding up the cord

Colours

profile powder coated white 9016 or silver 9006
side parts and control elements black or white

Lateral guiding

side guiding profile SunTape, 2 parts
anti-glare profile can be clipped
fabric fastening by tapes sealed onto the fabric edges
extruded aluminium profile
AlMgSi0,5 F22
dimensions 28 x 14 mm

Bottom bar

extruded aluminium profile
AlMgSi0,5 F22
dimensions 10 x 23 mm
inserted flat bar

Mounting

clip supports for wall- or ceiling mounting

Control

continuous control by pulling the cord knob when the cord is in diagonal position fabric is stopped by vertical cord guiding