				ORDER FORM			Roller blind system	Classic	
CUSTOMER				RECEIVE	R'S ADDRESS	3	DISPATCH	OFFER-NO.	
				Messrs.			UPS		
Custome	Customer/Client-No.							Please indicate, if an offer has been submitte	∌d.
Phone	Phone						Truck		
ı	T none				1				
Fax				Postal code Area			Pick up		
Person in charge				for the attn. of			Others	Stamp	
Commission				Delivery date				Date Signature	
ORD	ER sundrape® roller b	olinds are being	made to measure	and cannot be returne	ed nor exchanged.		Repeat! (If the fax has not be	een sent due to an error message)	
Pos.	Customer pos.	Pcs.	Туре по.	Roller blind width	Roller blind height	Colour Drapery/ aluminium parts quality	Operating Operation height* left right	Drilling Drilling tension wire Pri	ice
					_				
Electric components: To be ordered additionally! Additional components 8000:						000:		Further instructions:	
Not included in the roller blind delivery! Selection low voltage (24 V) acc. to data sheet page M 22 - M 23. Selection line voltage (230 V) acc. to data sheet page L 16 - L 17. Motor cable exit at the top					— ceiling clip — locking bar	ArtNo.: 505 765 505 040 nting bracket 500 760	W = wall mounting C = ceiling mounting N = niche mounting B = ground-/windowsill mounting		
beh	nind				adjustable mour	nting bracket 500 761		* Standard = 0,8 x blind height (rounding	g to 100 mm)