Order form

Roller blind system


	sundrape Uadro	M
--	-------------------	---

adro M		:
R-NO		


CUSTOMER		RECEIVER'S ADDRESS			DISPATCH		OFFER-NO.	
Contain of Citata Na					UPS L			
Customer/Client No.		Messrs.					Please indicate, if an offer has been submitted.	
Phone	Address			Truck				
L Fax	Postal code Area			Pick up				
Person in charge	for the attn. of					Stamp		
Commission				5 111010			Signatura .	
	nds are being made to m	Delivery date neasure and cannot be returned nor exchanged.			Date Signature Repeat! (If the fax has not been sent due to an error message)			·
Pos. Customer pos. Pcs.	Type no.	Roller blind width	l I	Colour (1) aluminium parts	Plastic parts black white	Drapery quality	Operating height (2)	Operation Support Price
	_ <u> M </u>						_	
	M							
	M							
	M							
	M							
Special operating elements side pull di stainless steel chain clip support with screws roller blind total width up to 1000 mm: 2 cli roller blind total width up to 1500 mm: 3 cli clamp support		Electric accessories see price list pcs. art. no.		Mounting roller blinds with head box SunTape lateral guiding, self adhesive in niche (only rectangular) SunTape lateral guiding, self adhesive on wall (only rectangular)		Advices: (1) silver 9006 or white 9016 (2) without information = 0,8 x height of blind (rounding to 100 mm) (3) without information = plastic ballchain colour according to plastic parts (4) mounting recommendation roller width up to 1000 mm: 2 fixing screws roller width up to 2000 mm: 4 fixing screws (Information for taking measurements please see overleaf)		




Roller blind without head box



freely suspended niche mounting




freely suspended wall mounting



freely suspended ceiling mounting

Take width of niche precisely. Consider overlap of drapery. We recommend 50 mm at each side.

Roller blind with head box



side pull drive or electric drive freely suspended wall mounting

Take width of niche

precisely. Consider


overlap of drapery.

50 mm at each side

We recommend


Take width of niche

precisely.



side pull drive or electric drive with tension wire quiding wall mounting

Take width of niche precisely. Consider overlap of drapery. We recommend 50 mm at each side.



side pull drive or electric drive with SunTape side quiding wall mounting

Take width of niche precisely.